

# OIL AND GREASE TREATMENT USING INDIGENOUS BACTERIAL BIOFILM SYSTEM

IEZZAT EMEER BIN AFFANDI

A thesis submitted in fulfilment of the  
requirements for the award of the degree of  
Master of Engineering (Bioprocess)

Faculty of Chemical Engineering  
Universiti Teknologi Malaysia

AUGUST 2014

**Specially dedicated to my beloved**  
Family, Lecturers and Friends

## ACKNOWLEDGEMENT

First and foremost, I would like to express my gratitude to Allah, the Almighty God for giving me the strength and guidance to accomplish this thesis. Alhamdulillah. I would like to thank to those who helped me during my Master's Degree.

I would like to express my deepest appreciation to my supervisor, Dr. Zainul Akmar Zakaria for his strong will, patience, commitment and guidance throughout my Master's Degree. His encouragement and meaningful advice will be remembered always. Special thanks to my co-supervisor, Prof Dr. Wan Azlina Ahmad with her dedication as never stop giving me moral support.

I am indebted to all lecturers and staff at Institute Bioproduct and Biodevelopment (IBD) and Faculty of Science (FS) for their assistance and support. Special thanks to my biotech and chemostatlab members for their assistance in this project. Thank you for the never ending support. Special thanks to my friends in UTM for the years of memorable and most enjoyable one.

Finally I would like to thank my lovely parents, Affandi Ghazali and Zahariah Mohamed for their unconditional love and dedication, especially at times when I need them most. Thanks to my siblings for their moral support and encouragement for me to become a role model. Special thanks to my dearest friend Siti Mariam Binti Abdul Lathiff for her motivation and moral support throughout the years.

## ABSTRACT

The Malaysian palm oil industry grows rapidly as the premier agriculture-based industry over the last two decades. However, the production of palm oil also resulted in the generation of large quantities of polluted wastewater commonly referred to as palm oil mill effluent (POME) as well as lignocellulosic biomass, especially from fronds, trunks, empty fruit bunch, palm kernel and mesocarp fibre. This study evaluates on the potential application of an immobilized bacterial-based system to reduce oil and grease (O&G) contamination in POME. From the 21 bacterial isolates, two isolates (i.e. isolate X7 and X10) were chosen for subsequent studies based on its high cell surface hydrophobicity, opaque halo formation and high culture turbidity. The bacterial isolates were evaluated for O&G degradation ability by varying contact time, initial POME concentration and initial pH. The isolated X10 showed the ability to completely degrade O&G from POME after 6 days of incubation at 200 rpm, 30°C and pH 7 in the batch study. In the continuous flow-through column study, oil palm frond (OPF) - immobilized isolate X7 showed complete O&G degradation and 92.59% of chemical oxygen demand (COD) degradation from 100% (v/v) POME used after 8 days of contact time. Scanning Electron Microscope examination showed the presence of diverse morphology of microorganisms indicating the formation of mature biofilm after 200 days. One of the bacterial species isolated from the biofilm was identified as *Bacillus cereus* in which match up to 99% of the query sequence. The finding of this study indicates the potential of using indigenous aerobic bacterial isolates as an alternative solution to degrade O&G in POME wastewaters.

## ABSTRAK

Industri minyak sawit Malaysia berkembang dengan pesat sebagai industri berasaskan pertanian yang terulung sejak dua dekad yang lalu. Walau bagaimanapun, pemprosesan minyak kelapa sawit juga menyebabkan penghasilan kuantiti air sisa tercemar yang banyak, seringkali dirujuk sebagai buangan air sisa kilang minyak sawit (POME) atau dikenali sebagai biojisim lignoselulosik, khususnya pelepah, batang, buah tandan kosong, isirong sawit dan gentian mesokarp. Kajian ini memberi tumpuan terhadap penilaian potensi sistem bakteria tersekat gerak untuk mengurangkan pencemaran minyak dan gris (O&G) dalam POME. Berdasarkan 21 pencilan bakteria awal, dua pencilan bakteria (iaitu pencilan X7 dan X10) telah dipilih untuk kajian selanjutnya berdasarkan nilai yang tinggi bagi permukaan sel, formasi halo legap dan nilai kekeruhan kultur. Pencilan bakteria telah dinilai bagi keupayaan menguraikan O&G dengan mempelbagaikan masa tindakbalas, kepekatan asal POME dan pH asal. Pencilan X10 menunjukkan keupayaan untuk mendegradasi secara lengkap O&G dari POME selepas tempoh penggeraman selama 6 hari pada 200 rpm, 30°C dan pH 7 menerusi kajian kelompok. Bagi kajian menggunakan aliran terus yang berterusan, pencilan X7 yang tersekat gerak pada pelepah kelapa sawit (OPF) menunjukkan keupayaan untuk mendegradasi secara lengkap O&G dan degradasi keperluan oksigen kimia (COD) pada tahap 92.59% daripada 100% (v/v) POME yang digunakan selepas 8 hari masa tindakbalas. Analisis mikroskop elektron pengimbas menunjukkan kehadiran morfologi pelbagai jenis mikroorganisma yang menandakan pembentukan biofilem matang selepas 200 hari. Salah satu daripada spesis bakteria yang diasingkan daripada biofilem telah dikenalpasti sebagai *Bacillus cereus* dengan nilai padanan setinggi 99%. Hasil daripada kajian ini menunjukkan potensi penggunaan pencilan bakteria indigenus aerobik sebagai penyelesaian alternatif untuk menguraikan O&G dalam air sisa buangan POME.